

Pegatanke Epoxy Putty

Date of compilation: 8/1/2022 Revised: 3/15/2024 Version: 2 (Replaced 1)

SECTION 1: IDENTIFICATION

1.1 GHS Product identifier:

Pegatanke Epoxy Putty

Other means of identification:

Not applicable (N/A)

1.2 Recommended use of the chemical and restrictions on use:

Relevant uses: Filler for repairing surfaces

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party:

PTKDELECUADOR S.A.

Av. 113, Calle Oliva Miranda y Calle 48, Multibodegas, Ofic. 6 y 7, Barrio Centenario

130204 Manta - Manabi - Ecuador

Phone: +593 5 2922174

info@pegatanke.com

https://pegatanke.com

1.4 Emergency phone number: Poison Help USA 1-800-222-1222.

SECTION 2: HAZARD(S) IDENTIFICATION

2.1 Classification of the substance or mixture:

This product contains less than 1% respirable crystalline silica, so it does not require classification

NFPA:

Health Hazards: 3

Flammability Hazards: 1

Instability Hazards: 0

Special Hazards: Not applicable (N/A)

HMIS®:

Health: 0

Flammability: 0

Physical Hazard: 0

Personal Protection:

29 CFR 1910.1200:

Classification of this product has been carried out in accordance with paragraph (d) of § 1910.1200.

Acute Tox. 3: Acute toxicity if swallowed, Category 3, H301

Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411

Comb. Dust: Combustible Dust, CD

Eye Dam. 1: Serious eye damage, Category 1, H318

Skin Corr. 1C: Skin corrosion, Category 1C, H314

Skin Sens. 1: Sensitisation, skin, Category 1, H317

STOT RE 2: Specific target organ toxicity, repeated exposure, Category 2, H373

2.2 Label elements:

NFPA:



HMIS®:

- CONTINUED ON NEXT PAGE -



Pegatanke Epoxy Putty

Date of compilation: 8/1/2022 Revised: 3/15/2024 Version: 2 (Replaced 1)

SECTION 2: HAZARD(S) IDENTIFICATION (continued)

HEALTH	0
FLAMMABILITY	0
PHYSICAL HAZARD	0
PERSONAL PROTECTION	

29 CFR 1910.1200:

Danger



Hazard statements:

Acute Tox. 3: H301 - Toxic if swallowed.
Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
Comb. Dust: May form combustible dust concentrations in air
Skin Corr. 1C: H314 - Causes severe skin burns and eye damage.
Skin Sens. 1: H317 - May cause an allergic skin reaction.
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand.
P102: Keep out of reach of children.
P264: Wash thoroughly after use.
P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.
P301+P330+P331: IF SWALLOWED: rinse mouth. Do NOT induce vomiting.
P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P501: Dispose of the contents/containers according to the local, state and federal regulations.

Additional labeling:

Federal Hazardous Substances Act (FHSA) >> Corrosive
Causes Burns. Do not swallow. Do not get in eyes. Do not get on skin or clothing. Do not breathe fumes. Handle with care. Keep out of reach of children. Wear gloves and safety glasses. Use only in a well-ventilated area.

FIRST AID TREATMENT

If swallowed, call a Poison Control Centre or doctor immediately. Do not induce vomiting. If in eyes, rinse with water for 15 minutes. If on skin, rinse well with water. If on clothes, remove clothes. If breathed in, move person to fresh air.

Contains : Bisphenol-A Epoxy Resin (epichlorohydrin) (CAS 25068-38-6); Secret; Secret 2; Benzyl alcohol (CAS 100-51-6).

Federal Hazardous Substances Act (FHSA) >> Strong sensitizer (dermal)

May cause an allergic skin reaction. Wear gloves. Keep out of reach of children.

FIRST AID TREATMENT

If on skin, rinse well with water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

Contains : Bisphenol-A Epoxy Resin (epichlorohydrin) (CAS 25068-38-6); Secret; Secret 2; Benzyl alcohol (CAS 100-51-6).

2.3 Hazards not otherwise classified (HNOC):

Not applicable (N/A)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances:

Non-applicable

3.2 Mixtures:

Chemical description: Mixture composed of additives, aggregates and resins in solvents

Components:

Remaining components are non-hazardous and/or present at amounts below reportable limits. The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret in accordance with paragraph (i) of §1910.1200. Therefore, in accordance with Appendix D to § 1910.1200, the product contains:

- CONTINUED ON NEXT PAGE -



Pegatanke Epoxy Putty

Date of compilation: 8/1/2022 Revised: 3/15/2024 Version: 2 (Replaced 1)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Identification		Chemical name	Concentration
CAS: 25068-38-6		Bisphenol-A Epoxy Resin (epichlorohydrin)	50 - <75 %
		Secret	15 - <30 %
		Secret 2	5 - <15 %
CAS: 100-51-6		Benzyl alcohol	<5 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST-AID MEASURES

4.1 Description of necessary measures:

Request medical assistance immediately, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Request medical assistance immediately, showing the SDS of this product. Induce vomiting (ONLY IN CONSCIOUS PEOPLE!) and then ingest large quantities of liquid to dilute the toxin. Keep the person affected at rest.

4.2 Most important symptoms/effects, acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of immediate medical attention and special treatment needed, if necessary:

Not applicable (N/A)

SECTION 5: FIRE-FIGHTING MEASURES

5.1 Suitable (and unsuitable) extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Specific hazards arising from the chemical:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Special protective equipment and precautions for fire-fighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

Additional provisions:

- CONTINUED ON NEXT PAGE -

Pegatanke Epoxy Putty

Date of compilation: 8/1/2022 Revised: 3/15/2024 Version: 2 (Replaced 1)

SECTION 5: FIRE-FIGHTING MEASURES (continued)

As in any fire, prevent human exposure to fire, smoke, fumes or products of combustion. Only properly trained personnel should be involved in firefighting. Evacuate nonessential personnel from the fire area. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Sweep up and shovel product or other means and place in container for reuse (preferred) or disposal

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and materials for containment and cleaning up:

For accidental releases in excess of reportable quantities (RQ) (Table 302.4), refer to 40 CFR 302 for detailed instructions concerning reporting requirements and notify the National Response Center (800) 424-8802.

Sweep up and shovel product or other means and place in container for reuse (preferred) or disposal

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and dispose of using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Due to its non-flammable nature, the product does not present a fire risk under normal conditions of storage, manipulation and use.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Preferably use aspiration for cleaning. Given the danger of the product by inhalation, any cleaning method that involves exposure to the product in this way (sweeping, etc.) is not recommended

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

NFPA 30: IIIB

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace:

Nuisance dust: Inhalable dust 10 mg/m³ // Respirable dust 4 mg/m³

8.2 Appropriate engineering controls:

- CONTINUED ON NEXT PAGE -



Pegatanke Epoxy Putty

Date of compilation: 8/1/2022 Revised: 3/15/2024 Version: 2 (Replaced 1)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

V.O.C.(weight-percent):	24 % weight
V.O.C. at 68 °F:	300.02 kg/m ³ (300.02 g/L)
South Coast Air Quality Management District (AQMD) - VOC Regulatory:	
V.O.C.(weight-percent):	24 % weight
V.O.C. at 68 °F:	300.02 kg/m ³ (300.02 g/L)
Ozone Transport Commission (OTC) Rules - VOC Regulatory:	
V.O.C.(weight-percent):	24 % weight
V.O.C. at 68 °F:	300.02 kg/m ³ (300.02 g/L)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 68 °F:	Solid
Appearance:	Paste
Color:	Black, Green
Odor:	Characteristic
Odour threshold:	Not applicable (N/A) *

Volatility:

Boiling point at atmospheric pressure:	Not applicable (N/A) *
Vapour pressure at 68 °F:	Not applicable (N/A) *
Vapour pressure at 122 °F:	Not applicable (N/A) *
Evaporation rate at 68 °F:	Not applicable (N/A) *

Product description:

Density at 68 °F:	1250 kg/m ³
Relative density at 68 °F:	1.123
Dynamic viscosity at 68 °F:	Not applicable (N/A) *
Kinematic viscosity at 68 °F:	Not applicable (N/A) *
Kinematic viscosity at 104 °F:	>20.5 mm ² /s
Concentration:	Not applicable (N/A) *
pH:	Not applicable (N/A) *
Vapour density at 68 °F:	Not applicable (N/A) *
Partition coefficient n-octanol/water 68 °F:	Not applicable (N/A) *
Solubility in water at 68 °F:	Not applicable (N/A) *
Solubility properties:	Partially water-soluble
Decomposition temperature:	Not applicable (N/A) *
Melting point/freezing point:	Not applicable (N/A) *

Flammability:

Flash Point:	298 °F
Flammability (solid, gas):	Not applicable (N/A) *
Autoignition temperature:	698 °F
Lower flammability limit:	Not applicable (N/A) *
Upper flammability limit:	Not applicable (N/A) *

*Not applicable (N/A) due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



Pegatanke Epoxy Putty

Date of compilation: 8/1/2022 Revised: 3/15/2024 Version: 2 (Replaced 1)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Above all, skin contact may occur as fabrics of all thicknesses can be destroyed, resulting in burns. For more information on the secondary effects see section 2.
- Contact with the eyes: Produces serious eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.
IARC: Not applicable (N/A)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Not applicable (N/A)

Specific toxicology information on the substances:

Identification		Acute toxicity	Genus
Bisphenol-A Epoxy Resin (epichlorohydrin) CAS: 25068-38-6	LD50 oral	>5000 mg/kg	
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>5 mg/L	
Secret	LD50 oral	51 mg/kg (ATEi)	Rat
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>20 mg/L	
Benzyl alcohol CAS: 100-51-6	LD50 oral	500 mg/kg (ATEi)	Rat
	LD50 dermal	2500 mg/kg	
	LC50 inhalation	1.5 mg/L (ATEi)	
Secret 2	LD50 oral	1200 mg/kg (ATEi)	Rat
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>20 mg/L	

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available
Toxic to aquatic life with long lasting effects.

- CONTINUED ON NEXT PAGE -



Pegatanke Epoxy Putty

Date of compilation: 8/1/2022 Revised: 3/15/2024 Version: 2 (Replaced 1)

SECTION 12: ECOLOGICAL INFORMATION (continued)

12.1 Ecotoxicity (aquatic and terrestrial, where available):

Acute toxicity:

Identification	Concentration	Species	Genus
Bisphenol-A Epoxy Resin (epichlorohydrin) CAS: 25068-38-6	LC50 > 1 - 10 mg/L (96 h)		Fish
	EC50 > 1 - 10 mg/L (48 h)		Crustacean
	EC50 > 1 - 10 mg/L (72 h)		Algae
Secret	LC50 63 mg/L (96 h)	Poecilia reticulata	Fish
	EC50 Not applicable (N/A)		
	EC50 43.94 mg/L (72 h)	Desmodesmus subspicatus	Algae
Secret 2	LC50 345 mg/L (96 h)	QSAR	Fish
	EC50 Not applicable (N/A)		
	EC50 Not applicable (N/A)		
Benzyl alcohol CAS: 100-51-6	LC50 646 mg/L (48 h)	Leuciscus idus	Fish
	EC50 400 mg/L (24 h)	Daphnia magna	Crustacean
	EC50 79 mg/L (3 h)	Scenedesmus subspicatus	Algae

Chronic toxicity:

Identification	Concentration	Species	Genus
Bisphenol-A Epoxy Resin (epichlorohydrin) CAS: 25068-38-6	NOEC Not applicable (N/A)		
	NOEC 0.3 mg/L	Daphnia magna	Crustacean
Benzyl alcohol CAS: 100-51-6	NOEC 48.897 mg/L	N/A	Fish
	NOEC 51 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Substance-specific information:

Identification		Degradability		Biodegradability	
Bisphenol-A Epoxy Resin (epichlorohydrin) CAS: 25068-38-6	BOD5	Not applicable (N/A)	Concentration	100 mg/L	
	COD	Not applicable (N/A)	Period	28 days	
	BOD5/COD	Not applicable (N/A)	% Biodegradable	0 %	
Secret	BOD5	Not applicable (N/A)	Concentration	100 mg/L	
	COD	Not applicable (N/A)	Period	28 days	
	BOD5/COD	Not applicable (N/A)	% Biodegradable	0 %	
Benzyl alcohol CAS: 100-51-6	BOD5	Not applicable (N/A)	Concentration	100 mg/L	
	COD	Not applicable (N/A)	Period	14 days	
	BOD5/COD	Not applicable (N/A)	% Biodegradable	94 %	

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
Bisphenol-A Epoxy Resin (epichlorohydrin) CAS: 25068-38-6	BCF	4
	Pow Log	2.8
	Potential	Low
Secret	BCF	20
	Pow Log	4.02
	Potential	Low
Secret 2	BCF	3
	Pow Log	0.77
	Potential	Low
Benzyl alcohol CAS: 100-51-6	BCF	0
	Pow Log	1.1
	Potential	Low

12.4 Mobility in soil:

- CONTINUED ON NEXT PAGE -



Pegatanke Epoxy Putty

Date of compilation: 8/1/2022 Revised: 3/15/2024 Version: 2 (Replaced 1)

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Absorption/desorption		Volatility	
Secret	Koc	9988	Henry	Not applicable (N/A)
	Conclusion	Immobile	Dry soil	Not applicable (N/A)
	Surface tension	Not applicable (N/A)	Moist soil	Not applicable (N/A)
Secret 2	Koc	15130	Henry	9.312E-12 Pa·m ³ /mol
	Conclusion	Immobile	Dry soil	No
	Surface tension	Not applicable (N/A)	Moist soil	No
Benzyl alcohol CAS: 100-51-6	Koc	Not applicable (N/A)	Henry	Not applicable (N/A)
	Conclusion	Not applicable (N/A)	Dry soil	Not applicable (N/A)
	Surface tension	3.679E-2 N/m (77 °F)	Moist soil	Not applicable (N/A)

Partially water-soluble

12.5 Results of PBT and vPvB assessment:

Non-applicable

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Disposal methods:

The next characteristic per RCRA could apply to the unused product if it becomes a waste material: Corrosivity. The next EPA hazardous waste number could apply: D002.

Wastes generated by normal household activities (e.g., routine house and yard maintenance) are excluded from the definition of hazardous waste (Title 40 of the Code of Federal Regulations Part 261.4)

Waste management (disposal and evaluation):

Follow RCRA framework and EPA regulation for to ensure that hazardous waste is managed safely and properly. Waste should not be disposed of to drains. Remind, it is the responsibility of the waste generator to evaluate whether his wastes are hazardous by characteristics or listing. See section 6 for further information about Accidental release measures.

Regulations related to waste management:

Legislation related to waste management:

40 CFR Solid Wastes - Part 239 through 282.

State regulatory requirements for generators may be more stringent than those in the federal program. Be sure to check the state 's policies.

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to 49 CFR on the Transport of Dangerous Goods:



14.1 UN number: UN2923
14.2 UN proper shipping name: CORROSIVE SOLID, TOXIC, N.O.S. (Secret; Bisphenol-A Epoxy Resin (epichlorohydrin))



14.3 Transport hazard class(es): 8
Labels: 8, 6.1

14.4 Packing group, if applicable: III

14.5 Marine pollutant: Yes

14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises

Physico-Chemical properties: see section 9

Limited quantities: 5 kg

Under 49 CFR 171.4, Except when transporting aboard a vessel, the requirements of this subchapter specific to marine pollutants do not apply to non-bulk packagings transported by motor vehicles, rail cars, and aircraft

14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code): Not applicable (N/A)

Transport of dangerous goods by sea:

- CONTINUED ON NEXT PAGE -






Pegatanke Epoxy Putty

Date of compilation: 8/1/2022 Revised: 3/15/2024 Version: 2 (Replaced 1)




SECTION 14: TRANSPORT INFORMATION (continued)

With regard to IMDG 41-22:

	14.1 UN number:	UN2923
	14.2 UN proper shipping name:	CORROSIVE SOLID, TOXIC, N.O.S. (Secret; Bisphenol-A Epoxy Resin (epichlorohydrin))
	14.3 Transport hazard class(es):	8
	Labels:	8, 6.1
	14.4 Packing group, if applicable:	III
	14.5 Marine pollutant:	Yes
	14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises	
	Special regulations:	274, 223
	EmS Codes:	F-A, S-B
	Physico-Chemical properties:	see section 9
	Limited quantities:	5 kg
	Segregation group:	Not applicable (N/A)
	14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):	Not applicable (N/A)

Transport of dangerous goods by air:

With regard to IATA/ICAO 2024:

	14.1 UN number:	UN2923
	14.2 UN proper shipping name:	CORROSIVE SOLID, TOXIC, N.O.S. (Secret; Bisphenol-A Epoxy Resin (epichlorohydrin))
	14.3 Transport hazard class(es):	8
	Labels:	8, 6.1
	14.4 Packing group, if applicable:	III
	14.5 Marine pollutant:	Yes
	14.6 Special precautions which a user needs to be aware of, or needs to comply with, in connection with transport or conveyance either within or outside their premises	
	Physico-Chemical properties:	see section 9
	14.7 Transport in bulk (according to Annex II of MARPOL 73/78 and the IBC Code):	Not applicable (N/A)

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations specific for the product in question:

- CALIFORNIA LABOR CODE - The Hazardous Substances List: *Secret 2*.
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Birth defects or other reproductive harm: Not applicable (N/A)
- California Proposition 65 (the Safe Drinking Water and Toxic Enforcement Act of 1986) - Cancer: Not applicable (N/A)
- CANADA-Domestic Substances List (DSL): *Bisphenol-A Epoxy Resin (epichlorohydrin) (25068-38-6)* ; Secret ; Secret 2 ; *Benzyl alcohol (100-51-6)*
- CANADA-Non-Domestic Substances List (NDSL): Not applicable (N/A)
- Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantities: Not applicable (N/A)
- Hazardous Air Pollutants (Clean Air Act): Not applicable (N/A)
- Massachusetts RTK - Substance List: *Benzyl alcohol (100-51-6)*
- Minnesota - Hazardous substances ERTK: Not applicable (N/A)
- New Jersey Worker and Community Right-to-Know Act: Not applicable (N/A)
- New York RTK - Substance list: Not applicable (N/A)
- NTP (National Toxicology Program): Not applicable (N/A)
- OSHA Specifically Regulated Substances (29 CFR 1910.1001-1096): Not applicable (N/A)
- Pennsylvania Worker and Community Right-to-Know Law: *Benzyl alcohol (100-51-6)*
- Rhode Island - Hazardous substances RTK: Not applicable (N/A)
- The Toxic Substances Control Act (TSCA) : *Bisphenol-A Epoxy Resin (epichlorohydrin) (25068-38-6)* ; Secret ; Secret 2 ; *Benzyl alcohol (100-51-6)*
- Toxic chemical release reporting under EPCRA section 313 (40 CFR Part 372): Not applicable (N/A)

- CONTINUED ON NEXT PAGE -

Pegatanke Epoxy Putty

Date of compilation: 8/1/2022 Revised: 3/15/2024 Version: 2 (Replaced 1)

SECTION 15: REGULATORY INFORMATION (continued)

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information provided in this safety data sheet as a foundation for conducting workplace-specific risk assessments. These assessments will help establish the appropriate risk prevention measures for handling, using, storing, and disposing of this product.

Other legislation:

Take into consideration other applicable federal, state, and local laws and local regulations.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with Appendix d to §1910.1200 - Safety data sheets

Texts of the legislative phrases mentioned in section 2:

H314: Causes severe skin burns and eye damage.

H318: Causes serious eye damage.

H317: May cause an allergic skin reaction.

H411: Toxic to aquatic life with long lasting effects.

H373: May cause damage to organs through prolonged or repeated exposure.

May form combustible dust concentrations in air

H301: Toxic if swallowed.

Advice related to training:

According to 29 CFR 1910.1200, training on chemical hazards is necessary for employees using this product. This training will facilitate their understanding and interpretation of the safety data sheet, as well as the product label.

Principal bibliographical sources:

Occupational Safety & Health Administration (OSHA).

Abbreviations and acronyms:

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association

ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5-day biochemical oxygen demand

BCF: Bioconcentration factor

LD50: Lethal Dose 50

CL50: Lethal Concentration 50

EC50: Effective concentration 50

Log-POW: Octanol-water partition coefficient

Koc: Partition coefficient of organic carbon

IARC: International Agency for Research on Cancer

Date of compilation: 8/1/2022

Revised: 3/15/2024

Manufacturer Disclaimer: The information contained in this safety data sheet ("SDS") is based on sources, technical knowledge and current legislation. Furthermore, is based on data believed to be accurate; thus, the company does not assume any liability for its accuracy. The information provided herein cannot be considered a guarantee of the properties of this product and the same is simply a description of the security requirements. The use, occupational methodology and/or conditions for users of this product are not within our awareness or control. It is ultimately the responsibility of the user(s) to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information of this SDS only refers to this product, which should not be used for purposes other than those specified. Finally, the manner in which this product is used and whether there is any infringement of patents is the sole responsibility of the user(s).

END OF SAFETY DATA SHEET